

PRODUCT INFORMATION SUMMARY

F032 : SELATE

ammonia free metallised polish stripper

Description of product

No choking ammonia fumes. Quick removal of all emulsion and metallised polishes even those 'aged on'. Controlled foam for use with suction driers and combined machines. Modern chelating action "unlocks" metallised polishes.

Product Uses

For the stripping of metallised and non-metallised polish from linoleum, rubber, sealed wood, terrazzo and thermoplastic floors. Effective heavy duty formulation for the removal of impacted dirt from concrete and non-porous surfaces.

Directions

Polish stripping - dilute Selite 1 part to 10 parts hot water. Allow to soak on floor for 10-15 minutes. Scrub thoroughly, preferably with a scrubbing machine fitted with a nylon scrubbing pad. Remove solution with a mop or suction drier. Rinse thoroughly and allow to dry before reapplying polish.

iNsignt Supported

iNsignt is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



typical dilution

iNsignt recommended product uses

Flooring - floor stripping / polish removal (machine)	1 : 10
Flooring - floor stripping / polish removal (mop)	1 : 10

Product Hazards and PPE Requirements

Danger



Contains : Sodium metasilicate

Risk Phrases

Causes severe skin burns and eye damage.

Safety Phrases

Keep out of reach of children. Wash hands thoroughly after handling. Wear eye protection, protective gloves, protective clothing. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention. Store locked up.

Technical Data

Composition	A fast acting formulation containing alkali builders, surfactants, penetrating agents, and sequestrants.
Appearance	Clear liquid
Colour	Blue
Cloud Point	38
Density	1.068
pH	>13.5
Stability	2 years in a unopened container

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industry-leading standards.
 - Selden minimises wastage, packaging and transportation.
 - If it can be recycled, it will be recycled.
 - Our chemicals policy exceeds regulatory requirements.
 - We don't expect other people to clean up after us.
 - Conserving energy, preserving resources.
 - By being innovative, we strive to do better.
 - We like to work in partnership with our clients.
- Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer

Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



ISO 9001



ISO 14001



ISO 18001

UKAS

accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

