## **Lovibond® Water Testing**

## Tintometer® Group



phone: +49 (0) 231 945100

E-Mail: sales@tintometer.de

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name: KS132 ALK3 Alkalinity HR Titrant
- · Catalog number: 56Z013298, 56L013265, 56U013265
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation: Reagent for water analysis
- · 1.3 Details of the supplier of the safety data sheet
- · Supplier:

Tintometer GmbH Schleefstr. 8-12 DE-44287 Dortmund Made in Germany www.lovibond.com

Informing department:

e-mail: produktsicherheit@tintometer.de

**Product Safety Department** 

· Contact for technical details:

**Technical Department** 

e-mail: technik@tintometer.de

· 1.4 Emergency telephone number:

Poison Center Berlin, Germany phone: 0049-30 30686 790 Languages: English and German

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labelling:

sulphuric acid 29.3 %

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

### Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P310 IF exposed or concerned: Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards No further relevant information available.
- · Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: aqueous solution

· Dangerous components:				
CAS: 7664-93-9 EINECS: 231-639-5 Index No: 016-020-00-8	sulphuric acid	Met. Corr.1, H290; Skin Corr. 1A, H314	25-35%	

· Additional information For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air.

Call a doctor immediately.

· After skin contact

Instantly wash with polyethylene glycol 400.

Instantly rinse with water.

Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing.

After eye contact

Rinse opened eye for several minutes (at least 15 min) under running water.

Call a doctor immediately.

· After swallowing

Rinse out mouth and then drink 1-2 glasses of water.

Do not induce vomiting; instantly call for medical help.

· 4.2 Most important symptoms and effects, both acute and delayed:

breathing difficulty

sickness

vomiting

diarrhoea

pain

strong caustic effect.

Danger

Danger of system failure.

Danger of gastric perforation.

Danger of pulmonary oedema.

· 4.3 Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs

Subsequent observation for pneumonia and pulmonary oedema

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture

The product is not combustible.

Formation of toxic gases is possible during heating or in case of fire.

Sulphur oxides (SOx)

(Contd. on page 3)

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

## Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 2)

## · 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ambient fire may liberate hazardous vapours.

## **SECTION 6: Accidental release measures**

- · 6.1 Personal precautions, protective equipment and emergency procedures
- · Advice for non-emergency personnel:

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Ensure adequate ventilation

Use breathing protection against the effects of fumes/dust/aerosol.

- · Advice for emergency responders: Protective equipment: see section 8
- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb with liquid-binding material (sand, diatomite, universal binders).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling
- · Advice on safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Hygiene measures:

Do not inhale gases / fumes / aerosols.

Do not get in eyes, on skin, or on clothing.

Take off immediately all contaminated clothing.

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke when using this product.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- · Requirements to be met by storerooms and containers: Store in cool location.
- · Information about storage in one common storage facility:

Store away from metals.

Do not store together with alkalis (caustic solutions).

Store away from flammable substances.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from the effects of light.

Protect from humidity and keep away from water.

- · Recommended storage temperature: 20 °C +/- 5 °C
- · 7.3 Specific end use(s) No further relevant information available.

GB -

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 3)

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:		
CAS: 7664-93-9 sulphuric acid		
WEL (Great Britain)	Long-term value: 0.05* mg/m³ *mist: defined as thoracic fraction	
IOELV (European Union)	Long-term value: 0.05 mg/m³	
OEL (Sweden)	Short-term value: 0.2 mg/m³ Long-term value: 0.1 mg/m³ C, V	

### · Regulatory information

WEL (Great Britain): EH40/2011

IOELV (European Union): 91/322/EEC, 2000/39/EC, 2006/15/EC

OEL (Sweden): AFS2015:7

#### DNELC

Derived No Effect Level (DNEL)

CAS: 7664-93-9 sulphuric acid			
Inhalative	DNEL	0.1 mg/m³ (Worker / acute / local effects)	
		0.05 mg/m³ (Worker / acute / systemic effects)	

### · Recommended monitoring procedures:

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norms DIN EN 482 and DIN EN 689.

#### · PNECs

Predicted No Effect Concentration (PNEC)

redicted no Ellect Concentration (FNEO)		
CAS: 7664-93-9 sulphuric acid		
PNEC	8.8 mg/l (Sewage treatment plant)	
	0.00025 mg/l (Marine water)	
	0.0025 mg/l (Fresh water)	
PNEC	0.002 mg/kg (Marine sediment)	
	0.002 mg/kg (Fresh water sediment)	

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Engineering measures:

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment. See item 7.

- · Personal protective equipment
- · Breathing equipment: Use breathing protection against the effects of fumes/dust/aerosol.
- · Recommended filter device for short term use: Filter P2
- · Protection of hands:

Acid resistant gloves

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.11$  mm

· Penetration time of glove material

Value for the permeation: Level = 1 ( < 10 min )

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Tightly sealed safety glasses.
- · Body protection: Acid resistant protective clothing
- · Limitation and supervision of exposure into the environment: Do not allow product to reach sewage system or water bodies.

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 4)

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and	d chemical properties		
· Appearance:			
Form / Physical state:	Fluid		
Colour:	Colourless		
· Odour:	Odourless		
· Odour threshold:	Not applicable		
· pH-value at 20 °C:	1		
<ul> <li>Melting point/Freezing point: Not determined</li> <li>Initial boiling point and boiling range: 295 °C</li> </ul>			
· Flash point:	Not applicable		
· Flammability (solid, gas):	Not applicable.		
· Decomposition temperature:	Not determined.		
· Auto-ignition temperature: Product is not self-igniting.			
<ul><li>Explosive properties:</li><li>Flammability or explosive limits:</li></ul>	Product is not explosive.		
Lower:	Not applicable		
Upper:	Not applicable		
· Oxidising properties:	none		
· Vapour pressure:	Not determined.		
Density at 20 °C:	1.2 g/cm <sup>3</sup>		
Relative density:	Not determined.		
· Vapour density:	Not determined.		
· Evaporation rate:	Not determined.		
· Solubility(ies):			
Water:	Fully miscible		
· Partition coefficient: n-octanol/water: Not determined.			
· Viscosity:	Not determined.		
· Solvent content: Organic solvents: Water:	0.0 % > 70 %		
· 9.2 Other information	No further relevant information available.		

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity see section 10.3
- · 10.2 Chemical stability Stable at ambient temperature (room temperature).
- · 10.3 Possibility of hazardous reactions

Corrosive action on metals

Reacts with metals forming hydrogen (--> Explosive!)

When diluting, always add acid to water, never vice versa

Diluting or dissolving in water always causes rapid heating

Reacts with reducing agents

Reacts with peroxides

Reacts with halogenated compounds

Reacts with oxidizing agents

Reacts with acids and alkali (lyes).

Reacts with ammonia (NH<sub>3</sub>).

· 10.4 Conditions to avoid

strong heating

Strong heating (decomposition)

· 10.5 Incompatible materials:

metals

combustible substances

organic solvents

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

Product name: KS132 - ALK3 - Alkalinity HR Titrant

· 10.6 Hazardous decomposition products: see section 5

(Contd. of page 5)

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values that are relevant for classification:

### CAS: 7664-93-9 sulphuric acid

Oral	LD50	2140 mg/kg (rat) (IUCLID)
Inhalative	LC 50	510 (pure) mg/m³/2h (rat) IUCLID

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eve damage.

· Serious eye damage/irritation

Causes serious eye damage.

Risk of blindness!

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) The following statements refer to the mixture:
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

## CAS: 7664-93-9 sulphuric acid

EC50 > 100 mg/l/48h (Daphnia magna) (OECD 202)

LC50 16-29 mg/l/96h (bluegill)

(Merck)

- · 12.2 Persistence and degradability .
- · Other information:

Mixture of inorganic compounds.

Methods for the determination of biodegradability are not applicable to inorganic substances.

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB), according to the criteria given in Annex XIII of Regulation (EC) No. 1907/2006.

· 12.6 Other adverse effects

Harmful effect due to pH shift.

Avoid transfer into the environment.

· Water hazard:

Mixture (Self-assessment acc. VwVwS Annex 4, German regulation):

Water hazard class 1: slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 6)

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to disposers of hazardous waste.

· European waste catalogue

16 05 07\* discarded inorganic chemicals consisting of or containing hazardous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

OFOTI	<b>SEL 4.4</b> 1	-			
SECTION	)NI 14-	Transpor	t in	ormat	ION
OLUIN	JIN 17.	Hallspoi		OHILIA	

	14.1	<b>UN-Number</b>
--	------	------------------

· ADR, IMDG, IATA UN2796

· 14.2 UN proper shipping name

· ADR 2796 SULPHURIC ACID · IMDG, IATA SULPHURIC ACID

· 14.3 Transport hazard class(es)

· ADR



· Class 8 (C1) Corrosive substances.

· Label

· IMDG, IATA



· Class 8 Corrosive substances.

· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA II

14.5 Environmental hazards: Not applicable.
 14.6 Special precautions for user Warning: Corrosive substances.

• Kemler Number: 80 • EMS Number: F-A,S-B

• EMS Number: F-A,S-E
• Segregation groups Acids
• Stowage Category B

· 14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

• Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2

· Tunnel restriction code E

(Contd. on page 8)

Printing date 13.03.2017 Version number 2 Revision: 13.03.2017

Product name: KS132 - ALK3 - Alkalinity HR Titrant

(Contd. of page 7)

· IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ)

1L

Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Regulation (EC) No 689/2008 concerning the export and import of dangerous chemicals:

None of the ingredients is listed.

· Regulation (EC) No 1005/2009 on substances that deplete the ozone layer:

None of the ingredients is listed.

- · Directive 2012/18/EU (SEVESO III):
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Information about limitation of use: Employment restrictions concerning young persons must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

- Training hints Provide adequate information, instruction and training for operators.
- · Abbreviations and acronyms:

STOT: specific target organ toxicity

SE: single exposure

RE: repeated exposure

EC50: half maximal effective concentration

IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of

Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr.1: Corrosive to metals - Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

- Sources Data arise from safety data sheets, reference works and literature.
- · \* Data compared to the previous version altered.